

# LED Interactive Touch Screen



## Specifications

Item Name	LED Interactive Touch Screen – MS Series			
LED Panel	LED Panel	65"	75"	86"
	Screen Type	LED		
	Resolution	4K UHD (3840 x 2160)		
	Color	10 bit 1.07B		
	Active Size	1428.48*803.52mm	1649.66*927.93mm	1895.04*1065.96 mm
	Brightness	450cd/m2		
	Contrast	5000:1 (according to panel brand)		
	Viewing Angle	178°		
	Display Protection	Anti-glare tempered glass		
	Backlight Lifetime	50,000 hours		
Camera	Camera	13 Megapixel Ultra HD		
Micro	Microphone	8 array microphone available for 8-10meters		
NFC	NFC Tag Reader	Support IC Card, ID Card		
Electrical performance	Max Power	≤250W	≤300W	≤400W
	Standby Power	≤0.5W		
	Voltage	110-240V(AC) 50/60Hz		
Operating System (Dual OS available)	Android System	Android 11.0 (Upgraded)		
		CPU: Cortex A55 / 1.9Ghz; GPU: Mali-G52 MP2 (Upgraded)		
		RAM: 8GB; ROM: 128G		
		Network: LAN/ WiFi 6 +5G		
		Bluetooth 5.0		
	OPS PC	Intel core i5 12 <sup>th</sup> Gen		
		Storage: Ram: 8G; Hard drive: 256 SSD		

		Intel integrated HD graphics	
		WIFI: 802.11b/g/n	
		Windows: Win 10 Pro with permanent copyright	
Touch	Touch Technology	IR touch; 20 points; HyPr Touch with Advanced IR	
	Response Speed	≤ 8ms	
	Accuracy	1mm	
	Operation System	20-Windows, Mac, and Android 10-Chrome OS	
Speakers	Power	20W*2	
Languages	Support	Chinese, English, French, Vietnamese...etc	
Software	Included	Whiteboard, Web Browser, Screen Sharing...etc	
Ports	Input Ports	PC HDMI 2.0*3; USB Type C*2; LAN (RJ45)*1; VGA*1; USB-A 3.0*2; USB-A 2.0*1; Touch USB-B 3.0*1; OPS slot*1; MicroSD*1; Stereo 3.5*1	
	Output Ports	HDMI 2.1*1; LAN (RJ45)*1; SPDIF*1; Stereo 3.5*1	
Working Environment	Working temperature	0°C-40°C	
	Storage temperature	- 20°C~60°C	
	Working humidity	10%-90% non-condensing	
Accessories	Power cable*1; Touch Pen*2; QC card*1; Warranty card*1; Remote Controller*1, AAA batteries*2, Cable USB 2.0 to B (5m)*1, Cable HDMI (5m)*1, Tool tray: With magnets, hanging on frame		
<b>Items / Model No.</b>	<b>FC-65LED-MS</b>	<b>FC-75LED-MS</b>	<b>FC-86LED-MS</b>
Product dimension	1490*906*85mm	1710*1030*85mm	1957*1170*95mm
Packing dimension	1620*1054*200mm	1845*1190*200mm	2110*1375*200mm
N.W/ G.W	~ 41kg/52kg	~ 56 kg/67 kg	~ 71 kg/82 kg